

5MP Fisheye Camera

DC-Y1514

- Easy installation with DirectIP NVR
- 5MP (2560 x 2048) resolution
- Fixed-focal lens (f=1.45 mm)
- micro SD/SDHC/SDXC, Smart Failover (Up to 128GB)
- Two-way audio
- Alarm In / out
- PoE (IEEE 802.3af Class 3), 12VDC
- Day and night (ICR)
- Various viewing composition, 6 dewarping view modes
- Supports ONVIF



SPECIFICATIONS

VIDEO		
Image Sensor	1/1.8" CMOS	
Max. Resolution	2560 x 2048	
Scanning Mode	Progressive Scan	
Lens Type	Fixed-focal	
Focal Length	f=1.45mm	
Aperture	F2.2	
Iris Control	Fixed Iris	
Angular Field of View	180° (H), 180° (V), 180° (D)	
Pan / Tilt Range	-	
Min. Illumination	Color : 0.8 Lux @ F2.2 B/W : 0.03 Lux @ F2.2	
Dynamic Range	More than 70dB	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)	
Day and Night	IR Cut Filter with Auto Switch	
IR Distance (LEDs)	-	
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR / 3DNR	
Backlight Compensation	On / Off / HSBLC	
Image Stabilizer	-	
Privacy Masking	16 Zones	
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	
Viewing Composition	10, 1P, 1P2R, 2P, 4R, 107R	
Video Out	-	
NETWORK		
	DirectIP Mode	Compatibility Mode
Video Compression	H.264 (MPEG-4 Part 10 / AVC), M-JPEG	
Intelligent Codec	Supported	
Bitrate Control	H.264 - VBR	
Audio Compression	ADPCM 16K, G.726, G.711 u-Law	
Two-way Audio	Yes	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Max. Frame Rate	30ips : 2560 x 2048	30ips : 2560 x 2048
Supported Resolution	2560 x 2048, 1536 x 1536, 640 x 512, 512 x 512	2560 x 2048, 1280 x 1024, 640 x 512, 2048 x 2048, 2048 x 1024, 1536 x 1536, 1024 x 1024, 1024 x 512, 512 x 512
Multi-video Streaming	Quadruple Streaming	Hextuple Streaming
Network Protocols	DirectIP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP, RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100/1000BASE-T)	
Recording Session Buffer (NLTRec)	Yes (Up to 100MB)	
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 128GB)	
ALARM AND EVENT		
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	
Event Notification	Remote S/W, Email (With Image)	
Audio In / Out	Line-in 1ea + Internal Mic 1ea / Line-out 1ea	
Alarm In / Out	Input 1ea / Output 1ea	
ENVIRONMENTAL		
Vandal Proof Casing	-	
Outdoor Ready	-	
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting Up at Above 0°C (32°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, PoE (IEEE 802.3af Class 3)	
Power Consumption	12V=, 0.63A, 7.56W PoE, IEEE 802.3af(Class 3)	
Approvals	FCC, CE, KC	
MECHANICAL		
Dimensions	Ø155mm x 43.0mm (Ø6.10" x 1.69")	
Weight	0.58kg (1.28lb)	

DIMENSIONS



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

