


Deliver
Intense Quality,
and Powerful
Image





RNZE-B501A





## **SPECIFICATIONS**

Model	3FECII IC	27(110143	
Lem		Model	RNZE-B501A
Min.   Busination   Cabe DEA to QUE FE (ACC DOS) ACC QUE FE (ACC DOS)		Image Sensor	CMOS
Day   Flight   Day   Flight   Day   EST		Lens	x33 ( 4.6-152mm )
Mode		Min. Illumination	Color: 0.03 lux @ F1.6 (AGC ON), B/W: 0 lux @ IR LED on
Processor   Proc	Camera	Day / Night	Dual ICR
Page		WDR	Digital WDR
Parting Range & Speed		IR Distance	150m
Paming Range & Speed		Image Setting	Configurable Brightness, Saturation, Contrast, HLC, Smart Defog, EIS
Titing Range & Speed		Optical Zoom	х33
Preset/ID		Panning Range & Speed	0* ~ 360*, Max. 240*/sec
Auto Panning	PTZ	Tilting Range & Speed	-16° ~ 90°, Max. 180°/sec
		Auto Panning	Mac. 8 scans
Video Compression		Preset/ID	500
Resolution   S011x 1000p(030ft)s, 960p(030ft)s, 770p(050ft)s   S011x 1010p(025ft)s, 560p(035ft)s, 560p(030ft)s   S011x 1010p(025ft)s, 560p(035ft)s   S011x 1010p(025ft)s   S011x 1010p(0		Group touring / Pattern	8/8
Max. Frame Rate   Multi-Streaming   30   30   30   30   30   30   30   3	Video/Audio	Video Compression	H.265, H.264 HP / MP / BP, M-JPEG
Video/Audio         Multi-Streaming         3           Video/Audio         A 2 arms           Privacy Mask / Motion Detection         Yes (Up to 4) / Yes           Video Analytics         Triprofer / Portimeter / Missing & Foreign chipet. / Crowd / Lostering / Fast Moring / Fast Moring / Fast Moring of Packing / Audio Offlice           For Overlay         Yes           Audio Compression         G.711A / G.711U / ADPCM / AAC           Tow-way Audio         Yes           Event         Event Trigger         Motion detection, IP Conflict, Port Alarm           Event         Event Notification         Relay out, Emal ETT Go to Preset           Pre/Post Event Buffering         Yes           Audio In / Out         1 br / 1 Out           Interface         Add In / Out         1 br / 1 Out           Storage         Micro SD (Up to 128 GB)           Security         Password protection, IP filter           Open Protocol         ONME (Profile S)           Post Col         Password protection, IP filter           Web Viewer         IEB In 10 LIT (Profile S)           Web Viewer         IEB In 10 LIT (Profile S)           Web Viewer         Mobile App (Profile S)           Web Viewer         Mobile App (Profile S)           Web Viewer         Mobile App (Profile S)		Resolution	
Video/Audio   Privacy Mark / Motion Detection   Yes Up to 4) / Yes		Max. Frame Rate	30fps@1920x1080,60fps@1280x720
Privacy Mask / Motion Detection		Multi-Streaming	3
Privacy Mask / Motion Detection		ROI (Region of Interest)	4 zones
Network   Fast Moving / Parking / Audio Offline		Privacy Mask / Motion Detection	Yes (Up to 4) / Yes
Audio Compression   G.711A / G.711U / ADPCM / AAC     Two-way Audio   Yes		Video Analytics	
Two-way Audio		Text Overlay	Yes
Event   Figger   Motion detection, IP Conflict, Port Alarm		Audio Compression	G.711A / G.711U / ADPCM / AAC
Event         Event Notification         Relay out, Email, FTP, Go to Preset           Pre/Post Event Buffering         Yes           Audio In / Out         1 In / 1 Out           Interface         Alarm In / Out         1 In / 1 Out           Storage         Micro SD (Up to 128 GB)           Ethernet         RJ-45 10/100BASE-T           Security         Password protection, IP filter           Open Protocol         ON/NF (Profile S)           Web Viewer         IP4 / IP6, HTTE, TEP, SMTP, UPR, SMTP, UPR, SMMP, DNS, DNS, NTP, RTSP, TCP, UDP, DHCP, PPPGE           Web Viewer         IE8, IE10, IE11, Chrome42 under version, Firefox 3.5 +           Video Management Software         Mobile App ((Phone, IPAC, Android))           Max. Connections         4 Level / 8 Users           Power Source         AC24V           Max. Power Consumption         27W (2200mA)           Operating Temperature / Humidity         -40°C -60°C / 0% - 95%RH           Standard Approvals         KC, LVD, CE           General         Language         Japanese, Korean, Chinese, English, Turkish, Spanish           Color / Material         White, Black / Diecasting           Ingress Protection         IP66           Dimension (Ø x H)         223mm x 372 mm		Two-way Audio	Yes
Pre/Post Event Buffering		Event Trigger	Motion detection, IP Conflict, Port Alarm
Network   Audio In / Out	Event	Event Notification	Relay out, Email, FTP, Go to Preset
Network   Fortical Protection   Fire Sum		Pre/Post Event Buffering	Yes
Storage   Micro SD (Up to 128 GB)	Interface	Audio In / Out	1 In / 1 Out
Retweet   RJ-45 10/100BASE-T		Alarm In / Out	1 In / 1 Out
Network   Protocol		Storage	Micro SD (Up to 128 GB)
Network   Protocol   ONVF (Profile S)	Network	Ethernet	RJ-45 10/100BASE-T
Network   Protocol   IPv4 / IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE		Security	Password protection, IP filter
NTP, RTSP, TCP, UDP, DHCP, PPPoE   Web Viewer		Open Protocol	ONVIF (Profile S)
Video Management Software       Mobile App (iPhone, iPad, Android)         Max. Connections       4 Level / 8 Users         AC24V         Max. Power Consumption       27W ( 2200mA )         Operating Temperature / Humidity       -40°C -60°C / 0% ~ 95%RH         Standard Approvals       KC, LVD, CE         Language       Japanese, Korean, Chinese, English, Turkish, Spanish         Color / Material       White, Black / Diecasting         Ingress Protection       IP66         Dimension (Ø x H)       223mm x 372 mm		Protocol	
Max. Connections  4 Level / 8 Users  AC24V  Max. Power Consumption 27W ( 2200mA )  Operating Temperature / Humidity 5 tandard Approvals  KC, LVD, CE  Language Japanese, Korean, Chinese, English, Turkish, Spanish  Color / Material Myhite, Black / Diecasting  Ingress Protection Dimension (Ø x H)  AC24V  AC24V  AC24V  AC220mA )  FWG, LVD, CE  Bapanese, Korean, Chinese, English, Turkish, Spanish  White, Black / Diecasting  IP66  Dimension (Ø x H)  223mm x 372 mm		Web Viewer	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+
Power Source         AC24V           Max. Power Consumption         27W ( 2200mA )           Operating Temperature / Humidity         -40°C -60°C / 0% ~ 95%RH           Standard Approvals         KC, LVD, CE           Language         Japanese, Korean, Chinese, English, Turkish, Spanish           Color / Material         White, Black / Diecasting           Ingress Protection         IP66           Dimension (Ø x H)         223mm x 372 mm		Video Management Software	Mobile App (iPhone, iPad, Android)
Max. Power Consumption         27W ( 2200mA )           Operating Temperature / Humidity         -40° C ~60° C / 0% ~ 95%RH           Standard Approvals         KC, LVD, CE           Language         Japanese, Korean, Chinese, English, Turkish, Spanish           Color / Material         White, Black / Diecasting           Ingress Protection         IP66           Dimension (Ø x H)         223mm x 372 mm		Max. Connections	4 Level / 8 Users
GeneralOperating Temperature / Humidity-40°C ~60°C / 0% ~ 95%RHStandard ApprovalsKC, LVD, CELanguageJapanese, Korean, Chinese, English, Turkish, SpanishColor / MaterialWhite, Black / DiecastingIngress ProtectionIP66Dimension (Ø x H)223mm x 372 mm	General	Power Source	AC24V
GeneralKC, LVD, CEGeneralLanguageJapanese, Korean, Chinese, English, Turkish, SpanishColor / MaterialWhite, Black / DiecastingIngress ProtectionIP66Dimension (Ø x H)223mm x 372 mm		Max. Power Consumption	27W ( 2200mA )
GeneralLanguageJapanese, Korean, Chinese, English, Turkish, SpanishColor / MaterialWhite, Black / DiecastingIngress ProtectionIP66Dimension (Ø x H)223mm x 372 mm		Operating Temperature / Humidity	-40°C ~60°C / 0% ~ 95%RH
Color / MaterialWhite, Black / DiecastingIngress ProtectionIP66Dimension (Ø x H)223mm x 372 mm		Standard Approvals	KC, LVD, CE
Ingress ProtectionIP66Dimension (Ø x H)223mm x 372 mm		Language	Japanese, Korean, Chinese, English, Turkish, Spanish
Dimension (Ø x H)         223mm x 372 mm		Color / Material	White, Black / Diecasting
		Ingress Protection	IP66
Weight 5.1kg (Camera Only)		Dimension (Ø x H)	223mm x 372 mm
		Weight	5.1kg (Camera Only)

💥 Exact products and specifications shown may vary by geographic region and are subject to change without notice. Actual products may differ from the images appearing in the catalog.



